


Gamme	CW & Modulated Lasers
Title	FlexxRay 458 nm
Reference	LBX-458
Description	The FlexxRay LBX-458 is a compact 458 nm laser source delivering one of the highest power available on the market over a beam of superior quality, and featuring a high-speed modulation. Its integrated control electronics and robust design suit both laboratory and industrial use. Performance, stability, and versatility make it a trusted solution for fluorescence-based microscopy, flow cytometry and illumination. Key features • TEM₀₀ spatial mode • ±0.5% long-term power stability; low optical noise • Modulation up to 150 MHz • Integrated control electronics • 100×40 mm industry-standard footprint Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.



Product Variations

Part Number	Puissance
LBX-458-500-CSB-PPA	500mW

Optical Characteristics

Emission wavelength	458 nm
Tolerance	(±5nm tolerance)
Control modes	Automated power control, Automated current control
Optical noise	? 0.2% rms, 10Hz-20MHz bandwidth
Spectral linewidth	? 1.5nm
Digital modulation function - Rise / fall time	? 2ns
Digital modulation function - Bandwidth	? 150MHz
Analog modulation function - Rise / fall time	? 150ns
Analog modulation function - Bandwidth	? 3MHz
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 ±0.2mm

Beam divergence, 1/e ² level full beam, far field	? 1.4mrad
Beam quality factor M ²	? 1.25
Beam circularity, far field	? 90%
Polarization state	Linear, vertical, extinction ratio ? 20dB

General Specifications

Power consumption	10W max.
Supply voltage	5V to 12V
Operating temperature	10°C to 50°C
Storage temperature and humidity	0°C to 60°C
Warm up time	?2 minutes
Interfaces	USB, RS-232, direct modulation inputs
Dimensions (laser head)	100x40x40 mm
Weight (laser head)	?330 g
Controler dimensions	106x126x56 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	4
Warranty	24 months or 10000 hours, whichever occurs first

Options

Option 1	Single-mode fiber coupling
Option 2	Multimode fiber coupling
Option 3	Heat management
Option 4	Electromechanical shutter
Option 5	Band-pass filter
Option 6	OEM version