


Gamme	CW & Modulated Lasers
Title	FlexxRay 561 nm (fixed power)
Reference	LCX-561L-PPF (fixed power)
Description	The FlexxRay LBX-561 is a compact 561nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use. Key features • TEM₀₀ spatial mode • ±1.0% long-term power stability • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.



Product Variations

Part Number	Puissance
LCX-561L-50-CSB-PPF	50mW
LCX-561L-100-CSB-PPF	100mW
LCX-561L-150-CSB-PPF	150mW
LCX-561L-200-CSB-PPF	200mW
LPX-561L-300-CSB-PPF	300mW
LPX-561L-500-CSB-PPF	500mW

Optical Characteristics

Emission wavelength	561 nm
Tolerance	(±0.4nm tolerance)
Control modes	Automated power control, fixed or adjustable power level
Optical noise	? 0.2% rms, 10Hz-20MHz bandwidth
Spectral linewidth	? 0.1nm
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 ±0.1mm
Beam divergence, 1/e² level full beam, far field	? 1.4mrad
Beam quality factor M²	? 1.1

Beam circularity, far field	? 90%
Polarization state	Linear, vertical,extinction ratio ? 20dB

General Specifications

Power consumption	20 W max.
Supply voltage	5V to 12V
Operating temperature	10°C to 50°C
Storage temperature and humidity	0°C to 60°C
Warm up time	?10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 300mW)120x40x32 mm (500mW and above)
Weight (laser head)	?300 g
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	3B, 4
Warranty	24 months or 10000 hours, whichever occurs first

Options

Option 1	Single-mode fiber coupling
Option 2	Multimode fiber coupling
Option 3	Heat management
Option 4	High rate modulation
Option 5	Optical Isolator
Option 6	OEM version