

FlexxRay

By Oxxius

Gamme	CW & Modulated Lasers
Title	FlexxRay 561 nm (adjustable power)
Reference	LCX-561L-PPA (adjustable power)
	<p>The FlexxRay LBX-561 is a compact 561nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use.</p> <p>Key features</p> <ul style="list-style-type: none">• TEM₀₀ spatial mode• ±1.0% long-term power stability• User-adjustable optical power• Integrated control electronics <p>Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.</p>
Description	



Product Variations

Part Number	Puissance
LCX-561L-50-CSB-PPA	50mW
LCX-561L-100-CSB-PPA	100mW
LCX-561L-150-CSB-PPA	150mW
LCX-561L-200-CSB-PPA	200mW
L1C+-561L-300-CSB-MPA	300mW
L1C+-561L-500-CSB-MPA	500mW

Optical Characteristics

Emission wavelength	561 nm
---------------------	--------

Tolerance	($\pm 0.4\text{nm}$ tolerance)
Control modes	Automated power control, fixed or adjustable power level
Optical noise	$\leq 0.5\%$ rms, 10Hz-20MHz bandwidth
Spectral linewidth	$\leq 0.1\text{nm}$
Beam diameter, $1/e^2$ level, 50mm from the beam aperture	$0.7 \pm 0.15\text{mm}$
Beam divergence, $1/e^2$ level full beam, far field	$\leq 1.4\text{mrad}$
Beam quality factor M^2	1.1
Beam circularity, far field	$\geq 90\%$
Polarization state	Linear, vertical, extinction ratio $\geq 20\text{dB}$

General Specifications

Power consumption	20 W max.
Supply voltage	5V to 12V (up to 200mW) 7V to 12V (300mW and above)
Operating temperature	10°C to 50°C
Storage temperature and humidity	0°C to 60°C
Warm up time	≤ 10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 200mW) 208x62x64 mm (300mW and above)
Weight (laser head)	≤ 250 g (up to 200mW) ≤ 1250 g (300mW and above)
Controller dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	3B, 4
Warranty	24 months or 10000 hours, whichever occurs first

Options

Option 1	Single-mode fiber coupling
Option 2	Multimode fiber coupling
Option 3	Heat management
Option 4	High rate modulation
Option 5	Optical Isolator
Option 6	OEM version