


FlexRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 532 nm (adjustable power)
Reference	LCX-532L (adjustable power)
Description	The FlexxRay LBX-532 is a compact 532nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use. Key features • TEM₀₀ spatial mode • $\pm 1.0\%$ long-term power stability • User-adjustable optical power • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.



Product Variations

Part Number	Power
LCX-532L-50-CSB-PPA	50mW
LCX-532L-100-CSB-PPA	100mW
LCX-532L-150-CSB-PPA	150mW
LCX-532L-200-CSB-PPA	200mW
L1C-532L-300-CSB-MPA	300mW
L1C+-532L-500-CSB-MPA	500mW
L1C+-532L-800-CSB-MPA	800mW

Optical Characteristics

Emission wavelength	532 nm
Tolerance	(± 0.3 nm tolerance)
Control modes	Automated power control, fixed or adjustable power level
Optical noise	$\leq 0.2\%$ rms (up to 300mW) $\leq 0.5\%$ rms (500mW and above), 10Hz-20MHz bandwidth
Spectral linewidth	≤ 0.1 nm
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 $\pm$ 0.15mm
Beam divergence, 1/e² level full beam, far field	≤ 1.4 mrad
Beam quality factor M²	1.1
Beam circularity, far field	$\geq 90\%$
Polarization state	Linear, vertical,extinction ratio ≥ 20 dB

General Specifications

Power consumption	20 W max.
Supply voltage	5V to 12V (up to 200mW)7V to 12V (300mW and above)
Operating temperature	10°C to 50°C
Storage temperature and humidity	0°C to 60°C
Warm up time	≤ 10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 200mW)154x62x64 mm (300mW)208x62x64 mm (500mW and above)
Weight (laser head)	≤ 250 g (up to 200mW) ≤ 1150 g (300mW) ≤ 1250 g (500mW and above)
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	3B, 4
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
Electromechanical shutter
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.