

FlexxRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 532 nm (fixed power)
Reference	LCX-532L (fixed power)
Description	<p>The FlexxRay LBX-532 is a compact 532nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use. Key features</p> <ul style="list-style-type: none"> • TEM₀₀ spatial mode • ±1.0% long-term power stability • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.



Product Variations

Part Number	Power
LCX-532L-50-CSB-PPF	50mW
LCX-532L-100-CSB-PPF	100mW
LCX-532L-150-CSB-PPF	150mW
LCX-532L-200-CSB-PPF	200mW
LCX-532L-300-CSB-PPF	300mW
LPX-532L-500-CSB-PPF	500mW
LPX-532L-800-CSB-PPF	800mW

Optical Characteristics

Emission wavelength	532 nm
Tolerance	(±0.3nm tolerance)
Control modes	Automated power control, fixed or adjustable power level
Optical noise	≤ 0.2% rms, 10Hz-20MHz bandwidth
Spectral linewidth	≤ 0.1nm
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 ±0.1mm
Beam divergence, 1/e² level full beam, far field	≤ 1.4mrad
Beam quality factor M²	1.1
Beam circularity, far field	≥ 90%
Polarization state	Linear, vertical,extinction ratio ≥ 20dB

General Specifications

Power consumption	20 W max.
Supply voltage	5V to 12V
Operating temperature	10°C to 50°C
Storage temperature and humidity	0°C to 60°C
Warm up time	≤10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 300mW)120x40x32 mm (500mW and above)
Weight (laser head)	≤300 g
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	3B, 4
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.