


FlexxRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 532 nm (fixed power)
Reference	LCX-532L (fixed power)
Description	<p>The FlexxRay LBX-532 is a compact 532nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use. Key features</p> <ul style="list-style-type: none"> • TEM₀₀ spatial mode • ±1.0 % long-term power stability • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.





Product Variations

Part Number	Power
LCX-532L-50-CSB-PPF	50 mW
LCX-532L-100-CSB-PPF	100 mW
LCX-532L-150-CSB-PPF	150 mW
LCX-532L-200-CSB-PPF	200 mW
LCX-532L-300-CSB-PPF	300 mW
LPX-532L-500-CSB-PPF	500 mW
LPX-532L-800-CSB-PPF	800 mW

Optical Characteristics

Emission wavelength	532 nm
Tolerance	(±0.3 nm tolerance)
Power stability over 8 hours, temperature within ±3°C	±1.0 %
Control modes	Automated power control, fixed or adjustable power level
Optical noise	≤0.2 % rms, 10 Hz-20 MHz bandwidth
Spectral linewidth	≤0.1 nm
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 ±0.mm
Beam divergence, 1/e² level full beam, far field	≤1.4 mrad
Beam quality factor M²	1.1
Beam circularity, far field	≥90 %
Polarization state	Linear, vertical, extinction ratio ≥20 dB

General Specifications

Power consumption	20 W max.
Supply voltage	5 V to 12 V
Operating temperature	10 °C to 50 °C
Storage temperature and humidity	0 °C to 60 °C
Warm up time	≤10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 300 mW) 120x40x32 mm (500 mW and above)
Weight (laser head)	≤300 g
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	 
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.