


FlexxRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 561 nm (adjustable power)
Reference	LCX-561L-PPA (adjustable power)
Description	<p>The FlexxRay LBX-561 is a compact 561 nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use. Key features</p> <ul style="list-style-type: none"> • TEM₀₀ spatial mode • ±0.5 % long-term power stability • User-adjustable optical power • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.





Product Variations

Part Number	Power
LCX-561L-50-CSB-PPA	50 mW
LCX-561L-100-CSB-PPA	100 mW
LCX-561L-150-CSB-PPA	150 mW
LCX-561L-200-CSB-PPA	200 mW
L1C+-561L-300-CSB-MPA	300 mW
L1C+-561L-500-CSB-MPA	500 mW

Optical Characteristics

Emission wavelength	561 nm
Tolerance	(±0.4 nm tolerance)
Power stability over 8 hours, temperature within ±3°C	±0.5 %
Control modes	Automated power control, fixed or adjustable power level
Optical noise	≤0.5 % rms, 10 Hz-20 MHz bandwidth
Spectral linewidth	≤0.1 nm
Beam diameter, 1/e² level, 50mm from the beam aperture	0.7 ±0.15 mm
Beam divergence, 1/e² level full beam, far field	≤1.4 mrad
Beam quality factor M²	1.1
Beam circularity, far field	≥90 %
Polarization state	Linear, vertical, extinction ratio ≥20 dB

General Specifications

Power consumption	20 W max.
Supply voltage	5 V to 12 V (up to 200 mW) 7 V to 12 V (300 mW and above)
Operating temperature	10 °C to 50 °C
Storage temperature and humidity	0 °C to 60 °C
Warm up time	≤10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 200 mW) 208x62x64 mm (300 mW and above)
Weight (laser head)	≤250 g (up to 200 mW) ≤1250 g (300 mW and above)
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	 
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.