


FlexxRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 561 nm (adjustable power)
Reference	LCX-561L-PPA (adjustable power)
Description	The FlexxRay LCX-561L-PPA is a compact 561 nm laser source delivering one of the highest power available on the market over a beam of superior quality. Its robust design, complete with readily available safety features makes it well-suited for both laboratory and industrial use.  Key features • TEM₀₀ spatial mode • ±0.5 % long-term power stability • User-adjustable optical power • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.

Product Variations

Part Number	Power
LCX-561L-50-CSB-PPA	50 mW
LCX-561L-100-CSB-PPA	100 mW
LCX-561L-150-CSB-PPA	150 mW
L1C-561L-200-CSB-PPA	200 mW
L1C+-561L-300-CSB-MPA	300 mW
L1C+-561L-500-CSB-MPA	500 mW

Optical Characteristics

Emission wavelength	561 nm
Tolerance	(± 0.4 nm tolerance)
Power stability over 8 hours, temperature within $\pm 3^{\circ}\text{C}$	± 0.5 %
Control modes	Automated power control, fixed or adjustable power level
Optical noise	≤ 0.5 % rms, 10 Hz-20 MHz bandwidth
Spectral linewidth	≤ 0.1 nm
Beam diameter, $1/e^2$ level, 50mm from the beam aperture	0.7 ± 0.15 mm
Beam divergence, $1/e^2$ level full beam, far field	≤ 1.4 mrad
Beam quality factor M^2	1.1
Beam circularity, far field	≥ 90 %
Polarization state	Linear, vertical, extinction ratio ≥ 20 dB

General Specifications

Power consumption	20 W max.
Supply voltage	5 V to 12 V (up to 200 mW) 7 V to 12 V (300 mW and above)
Operating temperature	10 $^{\circ}\text{C}$ to 50 $^{\circ}\text{C}$
Storage temperature and humidity	0 $^{\circ}\text{C}$ to 60 $^{\circ}\text{C}$
Warm up time	≤ 10 minutes
Interfaces	USB, RS-232
Dimensions (laser head)	100x40x32 mm (up to 200 mW) 208x62x64 mm (300 mW and above)
Weight (laser head)	≤ 250 g (up to 200 mW) ≤ 1250 g (300 mW and above)
Controler dimensions	109x84x30 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	 
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.