

FlexxRay

By Oxxius

Product range	CW & Modulated Lasers
Product name	FlexxRay 607 nm
Reference	LPX-607L
Description	The FlexxRay LPX-607 is a compact 607 nm laser source delivering one of the highest power available on the market over a beam of superior quality, and featuring an analogue modulation function. Its integrated control electronics and robust design suit both laboratory and industrial use. Performance, stability, and versatility make it a trusted solution for STED microscopy, optogenetics and fluorescence imaging. Key features • TEM₀₀ spatial mode • ± 1.0 % long-term power stability • Modulation up to 1.5 kHz • Integrated control electronics Fully compatible with Oxxius MixxWave combiners for single-mode fiber delivery alongside other laser lines.



Product Variations

Part Number	Power
LPX-607L-100-CSB-PPA	100 mW
LPX-607L-200-CSB-PPA	200 mW

Optical Characteristics

Emission wavelength	607 nm
Tolerance	(± 1 nm tolerance)
Power stability over 8 hours, temperature within $\pm 3^{\circ}\text{C}$	± 1.0 %
Control modes	Automated power control
Optical noise	$\leq 2.0\%$ rms, 10 Hz-100 kHz bandwidth
Spectral linewidth	≤ 0.5 nm
Digital modulation function - Rise / fall time	≤ 20 μs
Digital modulation function - Bandwidth	≥ 1.5 kHz
Analog modulation function - Rise / fall time	≤ 20 μs
Analog modulation function - Bandwidth	≥ 1.5 kHz
Beam diameter, $1/e^2$ level, 50mm from the beam aperture	0.7 ± 0.1 mm
Beam divergence, $1/e^2$ level full beam, far field	≤ 1.6 mrad
Beam quality factor M^2	≤ 1.1
Beam circularity, far field	≥ 90 %
Polarization state	Linear, vertical, extinction ratio ≥ 20 dB

General Specifications

Power consumption	20 W max.
Supply voltage	5 V to 12 V
Operating temperature	10 °C to 50 °C
Storage temperature and humidity	0 °C to 60 °C
Warm up time	≤5 minutes
Interfaces	USB, RS-232, direct modulation inputs
Dimensions (laser head)	120x40x32 mm
Weight (laser head)	250 g
Controler dimensions	106x126x56 mm
Compliance	CE (incl. IEC 60825-1) and FDA 21 CFR 1040.10 / 1040.11
Laser class	
Warranty	24 months or 10000 hours, whichever occurs first

Options

Single-mode fiber coupling
Multimode fiber coupling
Heat management
High rate modulation
Optical Isolator
OEM version

Oxxius has a policy of continuous product improvement. Specifications may change without notice.