


LBX-980-HPE Laser Diode



Optical characteristics *

Emission wavelength	980 nm	
Wavelength range	± 10 nm	
Linewidth	≤ 5 nm; 2 nm typical	
Output power	Free space	Fiber coupled
	1000 mW	800 mW
Control mode(s)	Automatic Current control (ACC)	
Power stability <small>over 8 hours and within ±3k</small>	± 1%	

— Transverse multimode free-space beam

Beam dimensions (typ) <small>at 1/e², at laser aperture</small>	3.5 X 1.5 mm
Beam divergence <small>at 1/e², full angle, in far field</small>	0.2 X 12 mrad

— Modulation functions

Analog Modulation

0-5V input voltage	
Bandwidth <small>3dB cut-off frequency, ACC mode</small>	DC-1 MHz
Rise/fall time, 10%-90%	≤ 200 ns


Fiber coupling option

	MM Fiber <small>(100 μm, 0.22 NA)</small>
Coupling Efficiency	≥ 80%
Available optical connector	AR-coated SMA FC-APC
Power stability <small>over 8 hours and within ±3k</small>	±2%
Fiber length	2.0 m

Warranty : 12 months from shipment date

*specification at nominal power

System specifications



— Plug and Play version provided with :

- ControlBoxx

Other options

- Heatsink. Including Power Supply
- L6Cc-HPE wavelength combiner compatibility
- Electro-mechanical shutter
- External modulator
- Specific beam shaping

General specifications

	Plug and Play version	OEM version
Compliance	CE FDA 21 CFR 1040.10/1040.1	FDA 21 CFR 1040.10 / 1040.11
Operating temperature	10 - 38°C ambient air with optional heat sink	10 - 50°C baseplate
Power consumption	≤ 25 W	≤ 10 W
Storage temperature	0 to 60°C	
Supply voltage	100 to 240 VAC external power supply	5 to 12 VDC
Warm-up time	≤ 2 minutes	
Interfaces	USB, RS-232, dedicated electronic interface	



CONTACT US

Oxxius S.A
4 rue Louis de Broglie
F-22300 Lannion, France

Phone : +33 296 48 70 28
sales@oxxius.com
www.oxxius.com